

Product name	Confidentiality level
E3372s	CONFIDENTIAL
Product version	Total 6 pages
V1.1	

E3372s Firmware Release Notes

V6.0

Prepared by	Baidabin	Date	2015-1-13
Reviewed by	Peng xiaolin	Date	2015-1-13
Approved by		Date	



Huawei Technologies Co., Ltd.

All rights reserved

Revision Record

Date	Revision version	FW-WebUI/Stick Version	Change Description	Author
2014-1-27	1.0	FW 21.270.99.01.00	First version	Wang runzhi
2014-2-7	2.0	FW 21.270.99.03.00	Second version	Wang runzhi
2014-3-3	3.0	FW 21.281.99.01.00	Third version	Wang runzhi
2014-4-3	4.0	FW 21.285.99.01.00	Fourth version	Wang runzhi
2014-4-19	5.0	FW 21.286.99.01.00	Fifth version	Wang runzhi
2015-1-13	5.0	FW 21.286.99.03.00	Sixth version	Bai dabin

Table of Contents

1	Main Features	4
2	Hardware.....	4
2.1	Hardware Specifications	4
3	Firmware.....	5
3.1	Version Description	5
3.2	Firmware Specifications	5
3.3	Improvement in the Previous Version	6
3.4	Known Limitations and Issues	6



E3372s Firmware Release Notes V1.0

1 Main Features

The E3372s supports the following standards:

- LTE cat4 data service up to 150Mbit/s (Downlink) and 50Mbit/s(Uplink)
- DC-HSPA+ data service up to 43.2 Mbit/s
- HSPA+ data service up to 21.6 Mbit/s
- HSDPA packet data service of up to 14.4 Mbit/s
- HSUPA data service up to 5.76 Mbit/s
- WCDMA PS domain data service of up to 384 Kbit/s
- Equalizer and receive diversity
- microSD Card Slot (Up to 32G)
- Data and SMS Service
- Plug and play
- Standard USB interface
- CSFB

2 Hardware

2.1 Hardware Specifications

Item	Specifications
Hardware Version	● CL1E3372SM
Technical standard	● LTE 3GPP R9 ● HSPA+/UMTS: 3GPP R99/R5/R6/R7/R8 ● GSM/GPRS/EDGE: 3GPP R99
External interfaces	USB: Type A with standard USB 2.0 High speed interface
	LED: indicating the status of the Data Card
	SD card: standard TF card interface
	SIM/USIM card: standard 6-pin SIM card interface
	RF interface: external RF interface
Maximum power consumption	≤ 3.5 W
Power supply	5V
Dimensions (D × W × H)	About 92mm(D) × 32mm(W) × 14mm (H)
Weight	≤ 50 g



Item	Specifications
Temperature	- Operating: -10°C to +40°C - Storage: -20°C to +70°C
Humidity	5% to 95%
Base Information	Plug and play (PnP)
	Standard USB 2.0 High Speed interface, auto installation, convenient for use
Note: 3GPP = The 3rd Generation Partnership Project TS = Technical Specification LED = Light-Emitting Diode SIM = Subscriber Identity Module USIM = UMTS Subscriber Identity Module	

3 Firmware

3.1 Version Description

Firmware Version:	21.286.99.03.00
Baseline information	Balong V7R2 C30B286

3.2 Firmware Specifications

Firmware		
Item	Specifications	
Version	21.286.99.03.00	
Information	Platform	Balong V7R2
	Baseline	C30B286
	Feature	LTE Supported
Data service	GSM CS domain	- Uplink: 9.6/14.4 kbit/s - Downlink: 9.6/14.4 kbit/s
	GPRS	- Uplink: 85.6 kbit/s - Downlink: 85.6 kbit/s
	EDGE	- Uplink: 236.8 kbit/s - Downlink: 236.8 kbit/s
	UMTS PS domain	- Uplink: 384 kbit/s - Downlink: 384 kbit/s
	HSDPA	14.4Mbit/s
	HSUPA	5.76 Mbit/s

Firmware		
Item	Specifications	
	HSPA+	• 21.6Mbit/s
	DC HSPA+	• Uplink:5.76 Mbit/s • Downlink:43.2Mbit/s
	LTE FDD	• Uplink: 50Mbit/s • Downlink:150Mbit/s
SMS	• SMS over SGs	
Operating System	• Windows XP/Windows Vista/WIN 7/MAC/WIN8	

3.3 Improvement in the Previous Version

Index	Case ID	Issue Description

3.4 Known Limitations and Issues

Index	Case ID	Issue Description